



Texas Rapids
 Average Velocity 36 Miles per Hour
 Maximum Velocity 114 Miles per Hour
 Backed up
 Submerged Reef

NOTE:
 SOUNDINGS ARE IN FEET AND THINGS NOT SHOWN HEREIN ARE ADAPTED
 LOW WATER PLUMB LINE ON U. S. WEATHER BUREAU GAGE AT RIVER
 ELEVATION 105 M. S. L.
 FIGURES IN PARENTHESES THUS (117) SHOW FEET ABOVE LOW WATER.
 ELEVATIONS ARE REFERRED TO MEAN SEA LEVEL 1,600.000 RATION 1929
 ACCORDING TO:
 CONTOUR INTERVAL 5 FEET.
 A FOOT DEPTH CURVE SHOWN THUS
 IS FOR USE IN CURVE SHOWN THUS
 CHANNEL LINE OF PROPOSED CHANNEL SHOWN THUS
 DISTANCE IN MILES FROM MOUTH OF RIVER MEASURED ON CENTER LINE OF
 PROPOSED CHANNEL SHOWN THUS (66)

**SNAKE RIVER, WASHINGTON - IDAHO
 MOUTH TO OREGON - WASHINGTON LINE
 REVIEW REPORT**

IN 54 SHEETS SCALE 12,000 SHEET NO. 60

U. S. ENGINEER OFFICE, PORTLAND, OREGON, 1934.

Submitted: *William L. Barr* Approved: *W. D. Thomas*
 Assistant Engineer Major, Corps of Engineers

Drawn by H. L. 1545C Transmitted with report dated June 10, 1935

SN-1-4/31
 H-9-2/80